



# Dura-Flex

- **.09" Wall Thickness Resists Snagging**
- **Prevents Damage From UV, Gasoline, Engine Chemicals and Salt**
- **Resists Cuts, Abrasion and Penetration**
- **Flexible & Economical General Purpose Protection**
- **Ideal For Home or Shop**
- **Deflects High Pressure Hose Ruptures**
- **No Damage After 100,000 Abrasion Cycles**

## Industrial Hose & Cable Protection For Harsh Environments

The tightly woven Nylon® makes DF the perfect solution for hose & cable protection. The .09 inch wall thickness will protect cables, hoses and ropes from weather, sunlight and abrasion damage.

When installed over uncoated cable or chains, DF will prevent scraping, chafing and contact damage to painted or other fragile surfaces.

DF is resistant to chemicals, UV damage and rot, and is suitable for continuous outdoor use under all weather conditions.

The flexible sleeving cuts with a scissor and the tight construction slides easily over any application.



Multiple high pressure hoses can be bundled tightly together to protect them from abrasion and weather, and to protect personnel from potential harm due to high pressure rupture.

Inside Diameter	Part #	Expansion Range		Bulk Lengths	Minimum Cuts	Available Colors	Lbs/100'
		Min.	Max.				
.71"	DFN0.71	This is a non-expandable product. Be sure to match your application diameter accurately.		100'	50'	Our standard, in-house color is Black. Custom colors are available per the chart on page 12. Ask your Account Rep for details.	2.57
.83"	DFN0.83		100'	50'	2.58		
1"	DFN1.00		100'	50'	3.66		
1.13"	DFN1.13		100'	50'	4.18		
1.25"	DFN1.25		100'	50'	4.49		
1.34"	DFN1.34		100'	50'	4.84		
1.59"	DFN1.59		100'	50'	5.37		
1.75"	DFN1.75		100'	50'	6.13		
2.07"	DFN2.07		100'	50'	7.26		
2.38"	DFN2.38		100'	50'	8.28		
2.54"	DFN2.54		100'	50'	8.98		
2.86"	DFN2.86		100'	50'	9.89		
3.34"	DFN3.34		50'	25'	11.59		
3.66"	DFN3.66		50'	25'	12.25		