

WISI DM 21 C

One-way tap, 8 dB



Description

Indoor mounting, screening factor class A, return path compatible

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern-Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 7. Juni 2016, 3:05 nachm.

Technical data

Frequency range	5...1000 MHz
Through loss	1,5...2,0 dB
Side loss	8 dB
Directional attenuation	30/25 dB (5...470/470...1000 MHz)
Return loss	18...22 dB

Connectors

F-socket	3 pcs. (1x input, 1x run through, 1x branch)
----------	--

General data

Screening factor (EMC)	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	no
Dimensions (width x height x depth)	55 x 50 x 28 mm

Packaging data

Sales unit	10 pcs.
Dimensions (WxHxD) sales unit	370 x 320 x 200 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.046 kg
Shipping unit	100 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	0.24 dm ³
Gross weight shipping unit	0.046 kg
EAN	4010056702991
Article number	70299
Customs tariff number	85291095