



ACCESSORIES F-Type Splitters

- High quality range of F-Type splitters from two to eight way
- Splitters are fully screened to EN50083-3 for high immunity
- Growing range of F-Type Taps and Splitters for system installations

Product range

- FS204 - 2-way splitter
- FS409 - 4-way splitter
- FS814 - 8-way splitter
- FS307 - 3-way splitter
- FS612 - 6-way splitter

Signal Splitters

Splitter	Frequency Range	Split Loss	Isolation	Return Loss	
FS204	2-way	40-950MHz	≤4.5dB	≤20dB	≤15dB
		950-2150MHz	≤6.0dB	≤18dB	≤14dB
FS307	3-way	40-950MHz	≤7.0dB	≤20dB	≤15dB
		950-2150MHz	≤9.0dB	≤18dB	≤10dB
FS409	4-way	40-950MHz	≤9dB	≤20dB	≤10dB
		950-2150MHz	≤12dB	≤18dB	≤11dB
FS612	6-way	40-950MHz	≤12dB	≤20dB	≤10dB
		950-2150MHz	≤16dB	≤18dB	≤11dB
FS814	8-way	40-950MHz	≤12dB	≤20dB	≤10dB
		950-2150MHz	≤16dB	≤18dB	≤11dB
Screening Factor	50-70MHz ≥75dB, 470-950MHz ≥65dB, 950-2150MHz ≥55dB				
Power Pass	30V DC, 1A Max (Via In & Out on taps, via In & one Output on splitters)				
Connections	75Ω "F" IEC60169-24 (f) Earth Terminal on all units				