## Reflex




- Highly Reflective
- Easy to Install
- Expands up to 150%
- Halogen Free
- Resists Gasoline and **Engine Chemicals**

## **Reflects On-Axis Light** 360° Up To 675'

FLEXO REFLEX (RF) is our polyethylene terepthalate material braided together with highly reflective 3M Scotchlite retroreflective monofilament. This unique combination provides a high level of wire and cable protection with the added advantage of extraordinary 360 degree, on-axis reflectivity.

RF is up to 1,500 times brighter than plain white under identical conditions and will provide high visibility safety on wires, hoses, cables, bicycle and motorcycle cables, stage wiring and virtually anything else up to 675' away. Reflective even under low light conditions. Patent pending.

| Nomin | I Part    | Expansion Range |        | Standard Spool Put-Ups |            | Available  | Lbs/ | -            |
|-------|-----------|-----------------|--------|------------------------|------------|------------|------|--------------|
| Size  | #         | Min.            | Max.   | Bulk Spool             | Shop Spool | Colors     | 100′ | 34 e         |
| 1/8″  | RFN0.13CL | 1/16″           | 1/4″   | 1,000′                 | 100′       | Clear (CL) | 0.29 |              |
| 1/4″  | RFN0.25   | 3/16″           | 3/8″   | 1,000′                 | 100′       | CL & BK    | 0.33 |              |
| 1/2″  | RFN0.50   | 1/4″            | 1″     | 500′                   | 100′       | CL & BK    | 0.52 | RoHS         |
| 3/4″  | RFN0.75   | 3/8″            | 1 3/8″ | 250′                   | 75′        | CL & BK    | 0.63 | Total States |



Under low light conditions, the retroreflective strands in FLEXO Reflex sleeving reflect light up to 1,500 times more efficiently than bright white sleeving.

## **F6** Reflex



Under low light conditions, the retrore-flective strands in FLEXO Reflex sleev-ing reflect light up to 1,500 times more efficiently than bright white sleeving.



installation

800 323-5140 www.techflex.com

## Reflective, Split Semi Rigid Sleeving For **Easy Installation**

Ease of installation make F6 REFLEX the most suitable reflective sleeving for applications where disassembly of the components is not a viable option. Just open the lateral split and slip the sleeving over wires or cables. The sleeving will snap back in place and provide an extra measure of safety under low light conditions. F6 Reflex is available in clear. Patents pending.

|   | Nominal | Part      | Wall      | Standard Sp | ool Put-Ups | Available | Lbs/ |  |
|---|---------|-----------|-----------|-------------|-------------|-----------|------|--|
|   | Size    | #         | Thickness | Bulk Spool  | Shop Spool  | Colors    | 100′ |  |
| Γ | 1/8″    | F6R0.13CL | .024″     | 400′        | 100′        | CL        | 0.20 |  |
|   | 1/4″    | F6R0.25CL | .025″     | 200′        | 100′        | CL        | 0.60 |  |
|   | 5/16″   | F6R0.31CL | .025″     | 150′        | 75′         | CL        | 0.75 |  |
|   | 1/2″    | F6R0.50CL | .025″     | 150′        | 75′         | CL        | 1.40 |  |

