

## Flexo PET-O

- Expands up to 200%
- Cut and Abrasion Resistant
- Halogen Free
- FMVSS 302 Approval

### Extra Expansion for Easy Application

FLEXO PET OVEREXPANDED (PT) has many uses where inexpensive bundling is the principal consideration. Created to provide a fast easy bundling solution for automotive and marine wiring. Overexpanded opens nearly 4 to 1 making it very easy to apply. The open construction allows the underlying harness or covering to show through for a unique and attractive assembly. The material cuts easily with either scissors or a hot knife.



Nominal Size	Part #	Expansion Range		Standard Spool Put-Ups		Available Colors	Lbs/100'
		Min.	Max.	Bulk Spool	Shop Spool		
1/4"	PTO0.25	1/8"	1/2"	1,000'	200'	BK	0.24
3/8"	PTO0.38	3/16"	1"	500'	125'	BK, CL, PP, NB, RD, NY, CB	0.52
1/2"	PTO0.50	7/16"	1 3/8"	500'	100'	CL & BK	0.63

## Flexo PET-T

- Complete Coverage
- Improved Abrasion Resistance

### Tight Weave for Extra Coverage

TIGHT WEAVE (PT) is designed for use in applications where optimum coverage and abrasion resistance is required. The tight braid construction increases the coverage, wear factor and improves harness security.



Nominal Size	Part #	Expansion Range		Standard Spool Put-Ups		Available Colors	Lbs/100'
		Min.	Max.	Bulk Spool	Shop Spool		
1/4"	PTT0.25BK	11/64"	11/32"	1,000'	200'	Black (BK)	0.36
5/16"	PTT0.31BK	23/64"	19/32"	1,000'	200'	Black (BK)	0.58
1/2"	PTT0.50BK	11/32"	5/8"	500'	100'	Black (BK)	0.84
3/4"	PTT0.75BK	1/2"	13/16"	250'	75'	Black (BK)	1.10
1"	PTT1.00BK	5/8"	1 1/8"	250'	65'	Black (BK)	1.23
1 1/4"	PTT1.25BK	1"	1 11/16"	250'	50'	Black (BK)	1.30
1 1/2"	PTT1.50BK	1 1/8"	2"	200'	40'	Black (BK)	1.95
1 3/4"	PTT1.75BK	1 1/2"	2 5/8"	200'	30'	Black (BK)	2.60
2"	PTT2.00BK	1 3/4"	3 1/8"	200'	50'	Black (BK)	3.43

