
## **F6 Woven Wrap**

- High Coverage
- Easy, Cost Effective Installation
- More Flexible than Split Convoluted or Spiral Wrap
- Cut and Abrasion Resistant

The Right Overlap For Your Harness



The engineered overlap allows ideal flexibility without exposing wires and cables.

## Woven, Split Tubular Harness Wrap

F6 Woven Wrap has been engineered from the ground up to meet the demanding specifications of today's modern wiring harness industry.

F6-WW utilizes many of the same characteristics as our original F6 split braided sleeving including the easy wrap around design and the extra overlap to insure complete protection of important electronic communication and power systems.

The new woven construction provides superior elastic flexibility with unbeatable coverage over any harness assembly. Wire harness professionals will also appreciate the increased abrasion resistance F6-WW will provide to their cable assemblies.



| Nominal<br>Size | Part<br># | Wall<br>Thickness | Standard Put-Ups |      |      | Available  | Overlap | Lbs/ |
|-----------------|-----------|-------------------|------------------|------|------|------------|---------|------|
|                 |           |                   | Bulk             | A    | В    | Colors     | *A ·    | 100′ |
| 3/16"           | F6W0.19BK | .027"             | 1,200′           | 600′ | 200′ | Black (BK) | 51%     | 0.98 |
| 5/16"           | F6W0.31BK | .027"             | 650′             | 325′ | 125′ | Black (BK) | 40%     | 1.30 |
| 3/8"            | F6W0.38BK | .027"             | 450′             | 225′ | 100′ | Black (BK) | 41%     | 1.50 |
| 1/2"            | F6W0.50BK | .027″             | 300′             | 150′ | 75′  | Black (BK) | 35%     | 1.80 |
| 5/8"            | F6W0.63BK | .027″             | 250′             | 125′ | 75′  | Black (BK) | 30%     | 2.10 |
| 3/4"            | F6W0.75BK | .027"             | 150′             | 100′ | 50′  | Black (BK) | 28%     | 2.40 |
| 1"              | F6W1.00BK | .027″             | 100′             | 75′  | 50′  | Black (BK) | 26%     | 3.20 |
| 1 1/2"          | F6W1.50BK | .027″             | 50′              | 25′  | -    | Black (BK) | 23%     | 4.50 |



