

# WISI DM 17 A

Passive headend combiner



## Description

### At a glance:

- Compact design, rack mounted
- High isolation
- Low insertion loss
- Full bandwidth from 5...1000 MHz
- Front panel test port for easy monitoring

#### WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7  
75223 Niefern-Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350  
E-Mail: [export@wisi.de](mailto:export@wisi.de)

Technical Modifications reserved. WISI cannot be held liable for any printing error. 7. Juni 2016, 3:05 nachm.

## Technical data

Frequency range	5...1000 MHz
Input impedance	75 $\Omega$
Input return loss	>18 dB typ., min. 14 dB
Number of taps	12
Output impedance	75 $\Omega$
Output return loss	>18 dB typ., min 13 dB
Tap loss IN-Out	1...12 < 18 dB ( $\pm$ 1,5 dB)
Amplitude response (O-E)	<1,5 dB
Isolation Out-Out	>40 dB typ., min. 36 dB
Test Port	-20 dB
RF-screening	>110 dB
Power passing	V DC none

## General data

Dimensions (width x height x depth)	483 x 44 x 124 mm
<b>Connectors</b>	
<b>Input</b>	1x F-connector
<b>Output</b>	12x F-connector
test	1x F-connector
Temperature range	-20...+55 °C

## Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	mm
Packaging volume sales unit	dm <sup>3</sup>
Gross weight sales unit	1,360 kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm <sup>3</sup>
Gross weight shipping unit	kg
EAN	4010056731960
Article number	73196
Customs tariff number	85291095