



# Turtle Wrap

- 13,500 Cycles\*
- 20 Mil Wall Thickness
- 1,000 Denier Cordura, Double Coated with Proprietary High FR Neoprene
- Extreme, Oversized Hook & Loop Closure
- Repels Liquids
- Prevents Damage From UV, Abrasion, Gasoline, Engine Chemicals And Salt Water
- Resists & Sheds Sparks And Hot Spall
- Non-Wicking

## Protection Sleeve with Easy On, Easy Off Hook And Loop Closure

TURTLE WRAP is made of 1,000 Denier Cordura, and double coated with proprietary high FR Neoprene. This protection sleeve is used for bundling and wrapping hoses and cables. The reusable sleeve features Mil-Spec extreme Hook & Loop closure which allows installation without disconnecting hoses and can reduce labor time by 70%.

TW is an excellent choice for weld cable or welding hose that is often dragged across the floor. This material resists sparks and hot spall. Turtle-Wrap is also used in Subsea maintenance where barnacles, sea life and salt water can damage hoses. This sleeve is also heavily used on off-shore oil rigs.



Nominal Size	Part #	Wall Thickness	Hook & Loop Width	Standard Spool Put-Ups		Available Colors	Lbs/100'
				Bulk Spool	Shop Spool		
1"	DWT1.00BK	.02"	1 1/4"	150'	25'	Black (BK)	
1 1/2"	DWT1.50BK	.02"	1 1/4"	150'	25'	Black (BK)	
1 3/4"	DWT1.75BK	.02"	1 1/4"	150'	25'	Black (BK)	
2"	DWT2.00BK	.02"	1 1/4"	150'	25'	Black (BK)	
2 3/8"	DWT2.38BK	.02"	1 1/4"	150'	25'	Black (BK)	
2 1/2"	DWT2.50BK	.02"	1 1/4"	150'	25'	Black (BK)	
3"	DWT3.00BK	.02"	1 1/4"	150'	25'	Black (BK)	
3 1/2"	DWT3.50BK	.02"	1 1/4"	150'	25'	Black (BK)	
4"	DWT4.00BK	.02"	1 1/4"	150'	25'	Black (BK)	
6"	DWT6.00BK	.02"	1 1/4"	150'	25'	Black (BK)	

800 323-5140  
www.techflex.com

*Abrasion Resistance						
630	950	2,500	3,500	4,400	8,500	13,000+
HIGH				EXTREMELY HIGH		

