



Flexo Stainless

Braided Stainless Steel, Pre-Rounded for Installation Ease

Nothing protects hoses from wear and blowout quite like real STAINLESS STEEL (SS) braid. It looks great in any application and is as strong as steel. But, custom hoses overbraided with stainless steel are expensive, selections are often limited and production and delivery times can be an issue.

Now, you can take any stock or custom hose, slip a length of Flexo Stainless over it, hide the cut ends under your clamps and have the same look and protection as custom overbraided hoses at a fraction of the cost.

Flexo Stainless cuts with shears or serrated scissors (pg. 73), is pre-rounded for easy, slip on installation and is available in diameters and expansion ranges to accommodate virtually any common hose or wire application.

Our new X-tra coverage product, Stainless Steel XC, provides fuller coverage and results in continuous stainless steel shine.

> Stainless Steel sleeving is used in applications such as expansion joints, where constant movement and high temperatures require a flexible, indestructible covering.



 Virtually Indestructible 304 Stainless Steel

- Won't Discolor or Rust
- Easy to Install
- Cuts with Shears or **Serrated Scissors**
- Resists Abrasion, **Chemicals and UV**
- Improves Burst **Strength of Hoses**



application and slides onto hoses for that cus tom look

Stainless Steel XC gives a full coverage on any



High end automotive applications have always used stainless steel hoses for looks, protection and durability

Flexo Stainless Steel

	Nominal Size	Part #	Wall Thickness	Expansion Range		Standard Spool Put-Ups		Available	Lbs/
				Min.	Max.	Bulk Spool	Shop Spool	Colors	100′
	1/2"	SSN0.50SV	.025"	1/4"	5/8"	100′	25′	Silver (SV)	4.00
-	5/8"	SSN0.63SV	.025"	3/8"	3/4"	100′	25′	Silver (SV)	5.00
-	3/4"	SSN0.75SV	.025"	1/2"	1″	100′	25′	Silver (SV)	5.00
-	1″	SSN1.00SV	.025"	3/4"	1 1/4"	100′	25′	Silver (SV)	11.00
-	1 1/4"	SSN1.25SV	.035"	1″	1 1/2"	100′	25′	Silver (SV)	19.00
	1 3/4"	SSN1.75SV	.040″	1 1/2"	2 1/4"	100′	25′	Silver (SV)	31.00

Flexo Stainless Steel XC

Nominal	Part #	Wall Thickness	Expansion Range		Standard Spool Put-Ups		Available	Lbs/
Size			Min.	Max.	Bulk Spool	Shop Spool	Colors	100′
1/8"	SSL0.13SV	.013"	1/16"	11/32"	250′	100′	Silver (SV)	1.20
1/4"	SSL0.25SV	.013"	3/16"	13/32"	250′	100′	Silver (SV)	2.20
3/8"	SSL0.38SV	.013"	1/4"	5/8"	250′	100′	Silver (SV)	2.54
1/2"	SSL0.50SV	.013"	3/8"	3/4"	100′	50′	Silver (SV)	3.15
3/4"	SSL0.75SV	.013"	1/2"	1 1/4"	100′	50′	Silver (SV)	6.90
1″	SSL1.00SV	.025"	5/8"	1 5/16"	100′	50′	Silver (SV)	9.78
1 1/4"	SSL1.25SV	.025"	3/4"	1 3/4"	100′	50′	Silver (SV)	13.70
1 1/2"	SSL1.50SV	.025″	1″	2 1/8"	100′	50′	Silver (SV)	16.60





800 323-5140 www.techflex.com