



- EMI, RFI, ESD Protection
- Grounding Straps
- Engine Dress-Up
- Complies With CID A-A-59569
- Extreme Blowout Protection
- Expands For Easy Installation
- Cut And Abrasion Resistant



Cut Cleanly  
Scissors

**Material**  
Tinned Copper

**Grade**  
MBN

**Wire Thickness**  
.005" - .010"

Nominal Size	Part #	Wall Thickness	Wire Thickness	Put-Ups		Available Colors	Lbs/100'
				Bulk Spool	Shop Spool		
1/16"	MBN0.06SV	0.013"	0.005"	250'	100'	Silver	0.40
7/64"	MBN0.11SV	0.013"	0.005"	250'	100'	Silver	0.80
1/8"	MBN0.13SV	0.013"	0.005"	250'	100'	Silver	1.00
5/32"	MBN0.16SV	0.013"	0.005"	250'	100'	Silver	2.10
11/64"	MBN0.17SV	0.013"	0.005"	250'	100'	Silver	1.35
13/64"	MBN0.20SV	0.020"	0.008"	250'	100'	Silver	2.50
1/4"	MBN0.25SV	0.013"	0.005"	250'	100'	Silver	2.20
3/8"	MBN0.38SV	0.013"	0.005"	250'	100'	Silver	3.30
1/2"	MBN0.50SV	0.013"	0.005"	100'	50'	Silver	3.50
5/8"	MBN0.63SV	0.016"	0.006"	100'	50'	Silver	3.60
25/32"	MBN0.78SV	0.013"	0.005"	100'	50'	Silver	7.35
7/8"	MBN0.88SV	0.025"	0.010"	100'	50'	Silver	10.30
1"	MBN1.00SV	0.025"	0.010"	100'	50'	Silver	13.15
1 1/8"	MBN1.13SV	0.025"	0.010"	100'	50'	Silver	13.80
1 1/4"	MBN1.25SV	0.025"	0.010"	100'	50'	Silver	16.50
1 3/8"	MBN1.38SV	0.025"	0.010"	100'	50'	Silver	16.90
1 1/2"	MBN1.50SV	0.025"	0.010"	100'	50'	Silver	18.40
2"	MBN2.00SV	0.025"	0.010"	100'	50'	Silver	22.70
2 1/4"	MBN2.25SV	0.025"	0.010"	100'	50'	Silver	23.60


**Tinned Copper Sleeve For Shielding, Grounding And Decoration. Provides Shield Coverage of 90% Minimum!**


Our skill with braided sleeving extends to many materials including metal braid for a variety of applications. Our tinned copper braid is perfect for shielding on harnesses and cables. Wire conforms to ASTM-B 33.

The material is also great for hose covering on hot rods and motorcycles.

(This product was previous known as Metal Braid.)


Colors Available:  
Silver (SV)





**Melt Point**  
ASTM D-2117

Copper 1,981°F (1,083°C)  
Tin 450°F (232°C)



**CHEMICAL RESISTANCE**

- 1=No Effect
- 2=Little Effect
- 3=Affected
- 4=More Affected
- 5=Severely Affected

Aromatic Solvents	1
Aliphatic Solvents	1
Chlorinated Solvents	1
Weak Bases	1
Salts	1
Strong Bases	2
Salt Water 0-S-1926	1
Hydraulic Fluid MIL-H-5606	1
Lube Oil MIL-L-7808	1
De-Icing Fluid MIL-A-8243	1
Strong Acids	5
Strong Oxidants	5
Esters/Ketones	1
UV Light	2
Petroleum	2
Fungus ASTM G-21	2
Halogen Free	Yes
RoHS	Yes

Nominal Size	Part #	AWG of Ends	Carriers	Wires Per Carrier	Current Capacity Amps
1/16"	MBN0.06SV	36	24	2	11
7/64"	MBN0.11SV	36	24	4	19
1/8"	MBN0.13SV	36	24	5	25
5/32"	MBN0.16SV	36	24	10	40
11/64"	MBN0.17SV	36	24	7	32
13/64"	MBN0.20SV	32	24	5	46
1/4"	MBN0.25SV	36	24	16	53
3/8"	MBN0.38SV	36	48	8	53
1/2"	MBN0.50SV	36	48	11	62
*5/8"	MBN0.63SV	34	48	8	64
25/32"	MBN0.78SV	36	48	18	88
7/8"	MBN0.88SV	30	48	7	100
1"	MBN1.00SV	30	48	8	120
1 1/8"	MBN1.13SV	30	48	9	130
*1 1/4"	MBN1.25SV	30	48	10	145
1 3/8"	MBN1.38SV	30	48	11	150
1 1/2"	MBN1.50SV	30	48	12	165
2"	MBN2.00SV	30	48	14	180
*2 1/4"	MBN2.25SV	30	48	16	190

\*Not on Spec - CID A-A-59569 (formerly Mil Spec QQB-575)

**PHYSICAL PROPERTIES**

Monofilament Diameter	.005-.010
ASTM D-204	
Flammability Rating	Non Flammable
Recommended Cutting	Shears
Colors	1
Wall Thickness	.013-.025
Specific Gravity ASTM D-792	8.9
Moisture Absorption	NA
% ASTM D-570	

**FLAMMABILITY**

Rating Non Flammable

© 2019 Techflex, Inc. - Any unauthorized reproduction, in whole or part, in any medium whatsoever, without the express written permission of Techflex, Inc. is strictly forbidden. Techflex product names and logos are registered trademarks of Techflex, Inc., unless otherwise attributed. The contents and illustrations contained herein are believed to be reliable. Techflex makes no warranties as to their accuracy or completeness and disclaims any liability in connection with their use. Techflex's only obligations are those in standard terms of sale for these products and Techflex will not be liable for any consequential or other damages arising due to misuse of these products or typographical errors or omissions. Users should make their own evaluation to determine the suitability of these products for their unique and specific applications.