



HEATSHRINK
TUBING

- Shrink Temp. 194°F
- Flame Retardant
- Versatile & Economical Termination Solution
- Resists Common Automotive Chemicals
- Easily Installs Over Connectors & Splices

4:1 Polyolefin Heatshrink Tubing

4:1 Shrinkflex heatshrink tubing is the most versatile of the heatshrink products. The high shrink ratio ensures that the tubing will slip over large connectors or plugs and still provide a tight, professional seal.

This high shrink ratio tubing shrinks 75% or more in the radial direction and 50% or less in the axial direction. Resistant to abrasion, chemicals, and oils, Shrinkflex tubing will ensure maximum protection while providing neat end terminations.



| Nominal Size | Part # | Unshrunk Diameter | Shrunk Diameter | Standard Spool Put-Ups | | Available Colors | Lbs/100' |
|--------------|-----------|-------------------|-----------------|------------------------|------------|------------------|----------|
| | | | | Bulk Spool | Shop Spool | | |
| 1/2" | H4N0.50BK | 12.0mm | 3.0mm | 200' | 25' | Black (BK) | 1.17 |
| 3/4" | H4N0.75BK | 19.0mm | 4.5mm | 100' | 25' | Black (BK) | 2.75 |
| 1" | H4N1.00BK | 25.4mm | 7.0mm | 100' | 25' | Black (BK) | 3.25 |
| 1 1/4" | H4N1.25BK | 32.0mm | 8.0mm | 100' | 25' | Black (BK) | 4.00 |
| 1 1/2" | H4N1.50BK | 38.0mm | 9.5mm | 100' | 25' | Black (BK) | 4.25 |



Ultra Clear 2:1 PVC Heatshrink Tubing

Shrinks to 1/2 its original diameter. Ultra clear PVC heatshrink tubing is ideal for applications where complete transparency is required.

PVC is perfect for protecting exposed wires and cables on motorcycles and custom automobiles. Resists gasoline, oil, and common chemicals; provides protection from abrasion and severe environments.



Stays clear when shrunk.

| Nominal Size | Part # | Unshrunk Diameter | Shrunk Diameter | Standard Spool Put-Ups | | Available Colors | Lbs/100' |
|--------------|-----------|-------------------|-----------------|------------------------|------------|------------------|----------|
| | | | | Bulk Spool | Shop Spool | | |
| 1/16" | H2P0.06 | 1.6mm | 0.8mm | 1,000' | 100' | CL & BK | 0.20 |
| 1/4" | H2P0.25 | 6.4mm | 3.2mm | 250' | 25' | CL & BK | 0.60 |
| 5/16" | H2P0.31 | 8.0mm | 4.0mm | 250' | 25' | CL & BK | 0.70 |
| 3/8" | H2P0.38 | 9.5mm | 4.8mm | 250' | 25' | CL & BK | 0.80 |
| 1/2" | H2P0.50 | 12.7mm | 6.4mm | 250' | 25' | CL & BK | 1.10 |
| 5/8" | H2P0.63 | 15.9mm | 7.9mm | 250' | 25' | CL & BK | 1.16 |
| 3/4" | H2P0.75 | 19.1mm | 9.5mm | 250' | 25' | CL & BK | 1.90 |
| 1" | H2P1.00 | 25.4mm | 12.7mm | 250' | 25' | CL & BK | 3.00 |
| 1 1/2" | H2P1.50 | 38.1mm | 19.1mm | 100' | 25' | CL & BK | 5.30 |
| 2" | H2P2.00 | 50.8mm | 25.4mm | 100' | 25' | CL & BK | 8.02 |
| 2 1/2" | H2P2.50CL | 63.5mm | 31.8mm | 100' | 25' | Clear CL | 9.45 |
| 3" | H2P3.00CL | 76.2mm | 38.1mm | 50' | 25' | Clear CL | 18.00 |

1-973-300-9242
www.techflex.com

Contact your account representative for heatshrink cutting & printing services.