

Splitters



9936



9937

Taps



9938



9939

Option switch

**new**



9218

- Plug-in switch to control 2 multiswitches for distribution of 16 SAT inputs with terrestrial to 1 user

## Splitters

Reference	9936	9937
Nb of inputs	4 SAT	4 SAT + 1 Terr
Nb of outputs	2 x 4	2 x 5
Frequency range	950-2300 MHz	Sat.: 950-2300 MHz Terr.: 5-862 MHz
Loss	5 dB	Sat.: 5 dB - Terr.: 5 dB
DC power pass in / out	yes	yes
Dimensions	158 x 142 x 51 mm	158 x 162 x 51 mm

## TAPS

Reference	9938	9939
Nb of inputs	4 SAT	4 SAT + 1 Terr
Nb of outputs	4 taps / 4 through	5 taps / 5 through
Frequency range	950-2300 MHz	Sat.: 950-2300 MHz Terr.: 5-862 MHz
Tap loss	-10 dB	Sat.: -10 dB - Terr.: -13 dB
Through loss	-1 dB	Sat.: -1 dB - Terr.: -1 dB
DC power pass in/tap/out	yes	yes
Dimensions	142 x 158 x 51 mm	162 x 158 x 51 mm

## Option switch

Reference	9218
Inputs	1 = SAT + TERR., 2 = SAT
Frequency range	SAT: 950-2300 MHz, TERR.: 5-862 MHz
Insertion loss	SAT: 4 dB± 1dB / Terr.: 3 dB
Isolation between inputs	26 dB min.
By pass control	22 kHz (universal band control) 13/18V (polar.) & position A/B
Switching control	Option A/B DiSEqC™ commands
Amplitude	0.6V ±0.2Vpp
Consumption	30 mA
DC loss	0.3V max.
Dimensions	110 x 65 x 20 mm